



## DK50 2x4VR/110 M (ADSORP)

### Specifications

<b>Frequency</b>	50 Hz
<b>Weight</b>	172 kg
<b>Dew Point</b>	-40 (PDP)
<b>Motor Input</b>	6,0 hp/4,4 kW
<b>LxWxH</b>	1210x770x1240 mm
<b>Tank Size</b>	110 l
<b>Current Consumption</b>	9,4 A
<b>Max. Pressure</b>	8 bar
<b>Voltage</b>	3x400 V
<b>Noise Level</b>	77 dB(A)/1m
<b>Protection Class</b>	IP20
<b>Duty Cycle</b>	S1 - 100%
<b>Air Flow @ 0 Bar</b>	629 (L/min)
<b>Air Flow @ 5 Bar</b>	459 (L/min)
<b>Air Flow @ 8 Bar</b>	408 (L/min)

### Description

The oil-free compressors from EKOM are designed and manufactured specific for the dental and medical industry but can also be used within many other industries. The compressors are very reliable and robust with a low noise level.

### Features

- Adsorption dryers (-40°C PDP) as option
- Membrane dryers (-20°C DP) as option
- Noise reducing cabinets for all models
- Robust and reliable solutions
- Long lifetime
- Noise level: 45–73 dB(A)/1m
- AC + DC solutions

