

## DK50 2x4VR/110 M (MEM)



### Specifications

<b>Frequency</b>	50 Hz
<b>Dew Point</b>	-20 (ADP)
<b>Motor Input</b>	6,0 hp/4,4 kW
<b>LxWxH</b>	1210x675x830 mm
<b>Weight</b>	158 kg
<b>Current Consumption</b>	9,4 A
<b>Max. Pressure</b>	8 bar
<b>Tank Size</b>	110 l
<b>Voltage</b>	3x400 V
<b>Noise Level</b>	77 dB(A)/1m
<b>Protection Class</b>	IP20
<b>Duty Cycle</b>	S1 - 100%
<b>Air Flow @ 0 Bar</b>	629 (L/min)
<b>Air Flow @ 5 Bar</b>	459 (L/min)
<b>Air Flow @ 8 Bar</b>	408 (L/min)

### Description

The oil-free compressors from EKOM are designed and manufactured specific for the dental and medical industry but can also be used within many other industries. The compressors are very reliable and robust with a low noise level.

### Features

- Adsorption dryers (-40°C PDP) as option
- Membrane dryers (-20°C DP) as option
- Noise reducing cabinets for all models
- Robust and reliable solutions
- Long lifetime
- Noise level: 45–73 dB(A)/1m
- AC + DC solutions

