



## DK50 2x4VR/110 S/M (ADSORP)

### Specifications

<b>Current Consumption</b>	9,4 A
<b>Frequency</b>	50 Hz
<b>Motor Input</b>	6,0 hp/4,4 kW
<b>Max. Pressure</b>	8 bar
<b>Noise Level</b>	58 dB(A)/1m
<b>Voltage</b>	3x400 V
<b>LxWxH</b>	1550x795x1240 mm
<b>Dew Point</b>	-40 (PDP)
<b>Weight</b>	252 kg
<b>Tank Size</b>	110 l
<b>Protection Class</b>	IP40
<b>Duty Cycle</b>	S1 - 100%
<b>Air Flow @ 0 Bar</b>	629 (L/min)
<b>Air Flow @ 5 Bar</b>	459 (L/min)
<b>Air Flow @ 8 Bar</b>	408 (L/min)

### Description

The oil-free compressors from EKOM are designed and manufactured specific for the dental and medical industry but can also be used within many other industries. The compressors are very reliable and robust with a low noise level.

### Features

- Adsorption dryers (-40°C PDP) as option
- Membrane dryers (-20°C DP) as option
- Noise reducing cabinets for all models
- Robust and reliable solutions
- Long lifetime
- Noise level: 45–73 dB(A)/1m
- AC + DC solutions

